AFX

beam100-LED MKII



Manufacturer	**AFX**
Type	**Moving head**
DMX modes	**1**
DMX footprint	**14 channels**
Beam angle	**25°**
Pan range	**530°**
Tilt range	**280°**
Size (W × H × D)	**240 × 450 × 220 mm**
GDTF fixture type	**75BA29D3-8681-4DE2-80B0-3F…**

Controls

Focus · Frost · Prism · Colour wheel · Strobe · Dimmer · Pan and tilt · Movement speed · Gobos

DMX modes

14 Channel — 14 ch

14 Channel

14 channels

Ch	Function	Default	DMX values
1	Pan	85	
2	Pan Fine	0	Fine byte of Pan
3	Tilt	128	
4	Tilt Fine	0	Fine byte of Tilt
5	Color Wheel	0	0–4 White (wheel slot 1) 5–9 White + Red (wheel slot 2) 10–14 Red (wheel slot 3) 15–19 Red + Yellow (wheel slot 4) 20–24 Yellow (wheel slot 5) 25–29 Yellow + Green (wheel slot 6) 30–34 Green (wheel slot 7) 35–39 Green + Purple (wheel slot 8) 40–44 Purple (wheel slot 9) 45–49 Purple + Cyan (wheel slot 10) 50–54 Cyan (wheel slot 11) 55–59 Cyan + Orange (wheel slot 12) 60–64 Orange (wheel slot 13) 65–69 Orange + Light Green (wheel slot 14) 70–74 Light Green (wheel slot 15) 75–79 Light Green + Pink (wheel slot 16) 80–84 Pink (wheel slot 17) 85–89 Pink + Blue (wheel slot 18) 90–94 Blue (wheel slot 19) 95–99 Blue + White (wheel slot 20) 100–177 Clockwise (wheel slot 21) 178–255 Anti Clockwise (wheel slot 22)
6	Gobo	0	0–4 Gobo 1 5–9 Gobo 2 10–14 Gobo 3 15–19 Gobo 4 20–24 Gobo 5 25–29 Gobo 6 30–34 Gobo 7 35–39 Gobo 8 40–44 Gobo 9 45–49 Gobo 10 50–54 Gobo 11 55–59 Gobo 12 60–64 Gobo 13 65–69 Gobo 14 70–74 Gobo 15 75–84 White Shake 85–89 Gobo Shake 1 90–94 Gobo Shake 2 95–99 Gobo Shake 3 100–104 Gobo Shake 4 105–109 Gobo Shake 5 110–114 Gobo Shake 6 115–119 Gobo Shake 7 120–124 Gobo Shake 8 125–129 Gobo Shake 9 130–134 Gobo Shake 10 135–139 Gobo Shake 11 140–144 Gobo Shake 12 145–149 Gobo Shake 13 150–154 Gobo Shake 14 155–159 Gobo Shake 15 160–207 Positive Flow Fast To Slow 208–255 Reverse Flow Slow To Fast

14 Channel (continued)

Ch	Function	Default	DMX values
7	Shutter / Strobe	255	0–3 Off 4–251 Strobe · Slow To Fast 252–255 Open
8	Dimmer	0	
9	Focus	0	
10	Prism	0	0–127 Prism 1 Out 128–255 Prism 1 In
11	Prism	0	0–127 Prism 2 Out 128–255 Prism 2 In
12	Frost1	0	0–127 Frost Out 128–255 Frost In
13	Position MSpeed	0	
14	Control1	0	