Briteq

BT-PROFILE 500TW



Manufacturer	**Briteq**
Type	**Profile spot**
DMX modes	**4**
DMX footprint	**1, 2, 3, 4 channels**
Beam angle	**22.2-40.5°**
Pan range	**360°**
Tilt range	**270°**
Size (W × H × D)	**238 × 550 × 238 mm**
GDTF fixture type	**91826299-4A0A-4E14-B70D-BB…**

Controls

Colour temperature · Strobe · Dimmer

Safety-relevant functions

Strobe

DMX modes

1Ch 8b	1 ch
2Ch 8b	2 ch
3Ch 16b	3 ch
4Ch 16bS	4 ch

1Ch 8b

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

2Ch 8b

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	C TC	23	0–9 2800K (wheel slot 1) 10–18 3000K (wheel slot 2) 19–27 3200K (wheel slot 3) 28–36 4000K (wheel slot 4) 37–45 4300K (wheel slot 5) 46–54 5600K (wheel slot 6) 55–63 6000K (wheel slot 7) 64–254 Min 255–255 Max

3Ch 16b

3 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Dimmer Fine	0	Fine byte of Dimmer
3	C TC	23	0–9 2800K (wheel slot 1) 10–18 3000K (wheel slot 2) 19–27 3200K (wheel slot 3) 28–36 4000K (wheel slot 4) 37–45 4300K (wheel slot 5) 46–54 5600K (wheel slot 6) 55–63 6000K (wheel slot 7) 64–254 Min 255–255 Max

4Ch 16bS

4 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Dimmer Fine	0	Fine byte of Dimmer
3	C TC	23	0–9 2800K (wheel slot 1) 10–18 3000K (wheel slot 2) 19–27 3200K (wheel slot 3) 28–36 4000K (wheel slot 4) 37–45 4300K (wheel slot 5) 46–54 5600K (wheel slot 6) 55–63 6000K (wheel slot 7) 64–254 Min 255–255 Max
4	Shutter / Strobe	0	0–5 Open 6–125 Strobe 126–135 NoFeature 1 136–255 Random strobe