Brother Brother and Sons

Force 7 EDLT 50 - 3000K



Manufacturer	**Brother Brother and Sons**
Type	**Profile spot**
DMX modes	**4**
DMX footprint	**1, 2, 3, 4 channels**
Beam angle	**36°**
Pan range	**360°**
Tilt range	**270°**
Size (W × H × D)	**160 × 120 × 160 mm**
GDTF fixture type	**5BC3C832-CCB4-488E-9116-29…**

Controls

Dimmer

DMX modes

8-bit	1 ch
16-bit	2 ch
8-bit - Strobe ON	3 ch
16-bit - Strobe ON	4 ch

8-bit

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

16-bit

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Dimmer Fine	0	Fine byte of Dimmer

8-bit - Strobe ON

3 channels

Ch	Function	Default	DMX values
1	Dimmer	0	
2	Strobe Mode Strobe	0	0–5 Open 6–125 Fast to Slow 126–130 Open 131–250 Random 251–255 Open
3	Strobe Duration	1	0–0 Off 1–24 0% 25–50 10% 51–76 20% 77–101 30% 102–127 40% 128–153 50% 154–178 60% 179–204 70% 205–229 80% 230–253 90% 254–254 99% 255–255 Off

16-bit - Strobe ON

4 channels

Ch	Function	Default	DMX values
1	Dimmer	0	
2	Dimmer Fine	0	Fine byte of Dimmer
3	Strobe Mode Strobe	0	0–5 Open 6–125 Fast to Slow 126–130 Open 131–250 Random 251–255 Open
4	Strobe Duration	1	0–0 Off 1–24 0% 25–50 10% 51–76 20% 77–101 30% 102–127 40% 128–153 50% 154–178 60% 179–204 70% 205–229 80% 230–253 90% 254–254 99% 255–255 Off