
Chauvet Professional

Ovation E-260 WW



Manufacturer	**Chauvet Professional**
Type	**Profile spot**
DMX modes	**4**
DMX footprint	**1, 2, 3, 6 channels**
Beam angle	**22°**
Size (W × H × D)	**257 × 349 × 34 mm**
GDTF fixture type	**BECD823C-490E-45A6-884F-58…**

Controls

Effect speed · Strobe · Dimmer

Safety-relevant functions

Fixture reset · Strobe · Built-in effect programmes

DMX modes

1Ch Mode	1 ch
2Ch Mode	2 ch
3Ch Mode	3 ch
6Ch Mode	6 ch

1Ch Mode

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–0 Min 1–254 Min > Max 255–255 Max

2Ch Mode

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	
2	Dimmer Fine	0	Fine byte of Dimmer

3Ch Mode

3 channels

Ch	Function	Default	DMX values
1	Dimmer	0	
2	Dimmer Fine	0	Fine byte of Dimmer
3	Shutter / Strobe	0	0–10 Open - Shutter Open 11–255 Strobe S > F - Strobe

6Ch Mode

6 channels

Ch	Function	Default	DMX values
1	Dimmer	0	
2	Dimmer Fine	0	Fine byte of Dimmer
3	Shutter / Strobe	0	0–10 Open - Shutter Open 11–255 Strobe S > F - Strobe
4	Effect	0	0–10 No Func - Custom 11–70 Auto 1 - Macro 71–130 Auto 2 - Macro 131–190 Auto 3 - Macro 191–255 Auto 4 - Macro
5	Effect Speed	0	0–0 Min 1–254 Min > Max 255–255 Max
6	Control1	0	0–7 No Function - Custom 8–15 Dimmer Reset - Reset 16–23 S-Curve Dimmer - Custom 24–31 Linear Dimmer - Custom 32–39 Square Dimmer Curve - Custom 40–47 Inverse Square Dimmer Curve - Custom 48–55 Dim Spd Mode Off - Speed 56–63 Dim Spd Mode 1 (Fastest) - Speed 64–71 Dim Spd Mode 2 - Speed 72–79 Dim Spd Mode 3 (Slowest) - Speed 80–87 Fan Auto - Custom 88–95 Fan On - Custom 96–103 Fan Off - Custom 104–111 Fan Silent - Custom 112–255 Reserved - Custom