Chauvet Professional

Ovation P-56VW



Manufacturer	**Chauvet Professional**
Type	**Moving head**
DMX modes	**1**
DMX footprint	**18 channels**
Beam angle	**25°**
Pan range	**540°**
Tilt range	**270°**
Size (W × H × D)	**220 × 350 × 210 mm**
GDTF fixture type	**0895440B-07B6-4501-B6B0-85…**

Controls

Extra LED colours · RGB colour mixing · Colour temperature · Strobe · Dimmer

Safety-relevant functions

Fixture reset · Strobe

DMX modes

Mode	18 ch

Mode

18 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Dimmer Fine	0	Fine byte of Dimmer
3	Red	255	0–127 Min 128–254 50% 255–255 Max
4	Red Fine	255	Fine byte of Red
5	Color Add RY	255	0–127 Min 128–254 50% 255–255 Max
6	Color Add RY Fine	255	Fine byte of Color Add RY
7	Green	255	0–127 Min 128–254 50% 255–255 Max
8	Green Fine	255	Fine byte of Green
9	UV	255	0–127 Min 128–254 50% 255–255 Max
10	UV Fine	255	Fine byte of UV
11	Blue	255	0–127 Min 128–254 50% 255–255 Max
12	Blue Fine	255	Fine byte of Blue
13	Color Add GY	255	0–127 Min 128–254 50% 255–255 Max
14	Color Add GY Fine	255	Fine byte of Color Add GY
15	Shutter / Strobe	0	0–10 No function 11–255 Strobe slow to fast

Mode (continued)

Ch	Function	Default	DMX values
16	C TC	0	0–5 No function 6–13 2800K 14–20 2900K 21–27 3000K 28–34 3100K 35–41 3200K 42–48 3300K 49–55 3400K 56–62 3500K 63–69 3600K 70–76 3700K 77–83 3800K 84–90 3900K 91–97 4000K 98–104 4100K 105–111 4200K 112–118 4300K 119–125 4400K 126–132 4500K 133–139 4600K 140–146 4700K 147–153 4800K 154–160 4900K 161–167 5000K 168–174 5100K 175–181 5200K 182–188 5300K 189–195 5400K 196–202 5500K 203–209 5600K 210–216 5700K 217–223 6000K 224–230 6500K 231–237 7000K 238–244 7500K 245–255 8000K
17	Tint	128	0–0 No function 1–127 -25 128–254 0 255–255 25
18	Control1	0	0–7 No function 8–15 Dimmer reset 16–23 Red shift on 24–31 Red shift off 32–39 S-curve dimmer 40–47 Linear dimmer 48–55 Square dimmer curve 56–63 Inverse square dimmer curve 64–71 Dimmer speed mode OFF 72–79 Dimmer speed 1 80–87 Dimmer speed 2 88–95 Dimmer speed 3 96–103 Fan auto 104–111 Fan on 112–119 Fan off 120–127 Fan silent 128–255 No function (reserved)