Chauvet Professional

WELL PANEL X



Manufacturer	**Chauvet Professional**
Type	**Effect light**
DMX modes	**1**
DMX footprint	**12 channels**
Beam angle	**21°**
Size (W × H × D)	**438 × 135 × 228 mm**
GDTF fixture type	**5A7C4297-299F-4FFA-969B-DD…**

Controls

Extra LED colours · RGB colour mixing · Colour temperature · Colour wheel · Effect speed · Strobe · Dimmer

Safety-relevant functions

Strobe · Built-in effect programmes

DMX modes

12ch — 12 ch

12ch

12 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Dimmer Fine	0	Fine byte of Dimmer
3	Shutter / Strobe	0	0–10 No function 11–255 Strobe slow to fast
4	Red	255	
5	Green	255	
6	Blue	255	
7	Color Add WW	255	
8	Color Wheel	0	
9	C TC	0	0–5 No function 6–25 2800K 26–50 3200K 51–75 3500K 76–100 4000K 101–125 4500K 126–150 5000K 151–175 5600K 176–200 6000K 201–225 6500K 226–255 No function
10	Effect	0	
11	Effect Speed	0	
12	Control1	0	0–10 No function 11–29 Reserved for future use 30–34 1000 Hz PWM 35–39 2000 Hz PWM 40–44 3000 Hz PWM 45–49 4000 Hz PWM 50–54 6000 Hz PWM 55–59 25 Khz PWM 60–69 Reserved for future use 70–74 S-Curve dimmer 75–79 Linear dimmer 80–84 Square dimmer 85–89 Inverse square dimmer 90–94 Dimmer speed off 95–99 Dimmer speed 1 100–104 Dimmer speed 2 105–109 Dimmer speed 3 110–149 Reserved for future use 150–154 Run time off 155–159 Run time 5h 160–164 Run time 8h 165–169 Run time 12h 170–174 Run time 18h 175–249 Reserved for future use 250–255 No function