CKC Lighting

IP PixBar 50WW



Manufacturer	**CKC Lighting**
Type	**PAR**
DMX modes	**2**
DMX footprint	**5, 8 channels**
Beam angle	**25-54°**
Size (W × H × D)	**695 × 58 × 50 mm**
GDTF fixture type	**7DCEB708-4CEE-4A03-889E-62…**

Controls

Extra LED colours · Strobe · Dimmer

Safety-relevant functions

Strobe

DMX modes

5CH	5 ch
8CH	8 ch

5CH

5 channels

Ch	Function	Default	DMX values
1	Shutter / Strobe	50	0–31 Closed 32–63 Open 64–94 min strobe 95–95 max strobe 96–127 open2 128–158 min pulse 159–159 max pulse 160–191 open3 192–222 min Random 223–223 max Random 224–255 open4
2	Dimmer	0	0–254 0% 255–255 100%
3	Dimmer Fine	0	Fine byte of Dimmer
4	Dimmer Mode	0	0–20 Halogen 21–40 LED 41–255 No Function
5	Control1	0	0–200 Idle 201–210 Dimmer Curve Linear(default) 211–220 Dimmer Curve Square 221–230 Dimmer Curve Inverse Square 231–240 Dimmer Curve S-Curve 241–255 Idle

8CH

8 channels

Ch	Function	Default	DMX values
1	Color Add WW	255	
2	Color Add WW Fine	255	Fine byte of Color Add WW
3	Color Add WW	255	
4	Color Add WW Fine	255	Fine byte of Color Add WW
5	Color Add WW	255	
6	Color Add WW Fine	255	Fine byte of Color Add WW
7	Color Add WW	255	
8	Color Add WW Fine	255	Fine byte of Color Add WW