
CLF Lighting

SoftLED100 VW



Manufacturer	**CLF Lighting**
Type	**Moving head**
DMX modes	**3**
DMX footprint	**2, 3, 5 channels**
Beam angle	**30°**
Pan range	**360°**
Tilt range	**180°**
Size (W × H × D)	**500 × 183 × 350 mm**
GDTF fixture type	**8267E224-4329-4913-B882-2A…**

Controls

Colour temperature · Strobe · Dimmer

DMX modes

2ch	2 ch
3ch	3 ch
5ch	5 ch

2ch

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	C TC	0	0–0 3200K 1–254 min to max 255–255 6000K

3ch

3 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	C TC	0	0–0 3200K 1–254 min to max 255–255 6000K
3	Shutter / Strobe	0	0–5 Open 6–6 Strobe · min 0.5 Hz 7–254 Strobe · min to max 0.578–19.9 Hz 255–255 Strobe · max 20 Hz

5ch

5 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Dimmer Fine	0	Fine byte of Dimmer
3	C TC	0	0–0 3200K 1–254 min to max 255–255 6000K
4	C TCPreset	0	0–10 from CTC Channel 11–30 3200K 31–50 4000K 51–70 5000K 71–90 5600K 91–110 6000K 111–160 User1 161–185 User2 186–210 User3 211–235 User4 236–255 User5
5	Shutter / Strobe	0	0–5 Open 6–6 Strobe · min 0.5 Hz 7–254 Strobe · min to max 0.578–19.9 Hz 255–255 Strobe · max 20 Hz