Eagle Lite

TP300 PRO



Manufacturer	**Eagle Lite**
Type	**Profile spot**
DMX modes	**3**
DMX footprint	**1, 2, 3 channels**
Beam angle	**14°**
Size (W × H × D)	**284 × 745 × 284 mm**
GDTF fixture type	**9E933D81-A1AF-4F9B-A1AE-D9…**

Controls

Strobe · Dimmer

Safety-relevant functions

Strobe

DMX modes

1 Channel Mode	1 ch
2 Channels Mode	2 ch
4 Channels Mode	3 ch

1 Channel Mode

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–62 MIn 63–126 25% 127–190 50% 191–254 75% 255–255 Max

2 Channels Mode

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–62 MIn 63–126 25% 127–190 50% 191–254 75% 255–255 Max
2	Shutter / Strobe	0	0–1 Open 2–255 Strobe 0-100%

4 Channels Mode

3 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–63 MIn 64–127 25% 128–190 50% 191–254 75% 255–255 Max
2	Dimmer Fine	0	Fine byte of Dimmer
3	Shutter / Strobe	0	0–1 Open 2–255 Strobe 0-100%