EK Lights

EProfile HP



Manufacturer	**EK Lights**
Type	**Profile spot**
DMX modes	**3**
DMX footprint	**1, 2, 5 channels**
Beam angle	**25°**
Size (W × H × D)	**240 × 625 × 240 mm**
GDTF fixture type	**9269937F-A276-424E-966B-A1…**

Controls

Effect speed · Strobe · Dimmer

Safety-relevant functions

Strobe · Built-in effect programmes

DMX modes

1CH	1 ch
2CH	2 ch
5CH	5 ch

1CH

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

2CH

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–10 Open 11–255 Strobe

5CH

5 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–10 Open 11–255 Strobe
3	Effect	0	0–10 No Function 11–70 Auto Program 1 71–130 Auto Program 2 131–190 Auto Program 3 191–255 Auto Program 4
4	Effect Speed	0	
5	Dimmer Curve	0	0–51 Menu Set 52–101 Dim Curve Off 102–152 Curve 1 (Fast) 153–203 Curve 2 (Mid) 204–255 Curve 3 (Slow)