Elation

Proton 3K



Manufacturer	**Elation**
Type	**Strobe**
DMX modes	**4**
DMX footprint	**1, 2, 3, 4 channels**
Beam angle	**50°**
Size (W × H × D)	**422 × 175 × 240 mm**
GDTF fixture type	**F3FC9DB7-BDA3-42AA-81A0-7…**

Controls

Dimmer

Safety-relevant functions

Built-in effect programmes

DMX modes

1 Channel	1 ch
2 Channel	2 ch
3 Channel	3 ch
4 Channel	4 ch

1 Channel

1 channel

Ch	Function	Default	DMX values
1	Strobe Rate	0	0–5 No flash 6–250 Slow to Fast 251–255 Continuous BLINDER effect

2 Channel

2 channels

Ch	Function	Default	DMX values
1	Strobe Rate	0	0–5 No flash 6–250 Slow to Fast 251–255 Continuous BLINDER effect
2	Dimmer	0	0–5 Blackout 6–46 1 % 47–117 25 % 118–184 50 % 185–254 75 % 255–255 100 %

3 Channel

3 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–5 Blackout 6–46 1 % 47–117 25 % 118–184 50 % 185–254 75 % 255–255 100 %
2	Strobe Duration	0	0–0 0 ms 1–255 1ms to 650 ms
3	Strobe Rate	0	0–5 No flash 6–129 05 Hz 130–254 12 Hz 255–255 25 Hz

4 Channel

4 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–5 Blackout 6–46 1 % 47–117 25 % 118–184 50 % 185–254 75 % 255–255 100 %
2	Strobe Duration	0	0–0 0 ms 1–255 1ms to 650 ms
3	Strobe Rate	0	0–5 No flash 6–129 05 Hz 130–254 12 Hz 255–255 25 Hz
4	Effect	0	0–5 No Effect 6–42 Ramp UP 43–85 Ramp DOWN 86–128 Ramp UP-DOWN 129–171 Random 172–214 Lighting 215–255 Spikes