ETC

Colorsource Spot V



Manufacturer	**ETC**
Type	**Profile spot**
DMX modes	**4**
DMX footprint	**1, 3, 7, 9 channels**
Beam angle	**27°**
Size (W × H × D)	**191 × 676 × 206 mm**
GDTF fixture type	**D493FCC1-F010-4F7C-9F46-6D…**

Controls

Extra LED colours · RGB colour mixing · Dimmer

DMX modes

1CH	1 ch
RGB	3 ch
Standard	7 ch
Direct	9 ch

1CH

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

RGB

3 channels

Ch	Function	Default	DMX values
1	Red	0	
2	Green	0	
3	Blue	0	

Standard

7 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Red	255	
3	Green	255	
4	Blue	255	
5	Strobe Mode Strobe	0	0–0 No Strobe 1–40 Dark Strobe 41–80 Bright Strobe 81–120 Pulse Strobe 121–160 Random Strobe 161–200 Flicker Effect 201–240 No Strobe 241–254 LEDs Off 255–255 No Strobe
6	Fan Mode	0	0–9 Auto 10–19 Off 20–20 Slow 21–248 Linear Increase in Speed 249–249 Fast 250–255 Auto
7	Dimmer Curve	0	0–9 Incandescent 10–19 Linear 20–29 Incandescent Red Shift 30–39 Linear Red Shift 40–49 Quick 50–59 Quick Linear 60–69 Unregulated 70–79 Standard 80–255 Reserved

Direct

9 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Red	255	
3	Green	255	
4	Blue	255	
5	Color Add BM	255	
6	Color Add GY	255	

Direct (continued)

Ch	Function	Default	DMX values
7	Strobe Mode Strobe	0	0–0 No Strobe 1–40 Dark Strobe 41–80 Bright Strobe 81–120 Pulse Strobe 121–160 Random Strobe 161–200 Flicker Effect 201–240 No Strobe 241–254 LEDs Off 255–255 No Strobe
8	Fan Mode	0	0–9 Auto 10–19 Off 20–20 Slow 21–248 Linear Increase in Speed 249–249 Fast 250–255 Auto
9	Dimmer Curve	0	0–9 Incandescent 10–19 Linear 20–29 Incandescent Red Shift 30–39 Linear Red Shift 40–49 Quick 50–59 Quick Linear 60–69 Unregulated 70–79 Standard 80–255 Reserved