Expolite

Tour-LED Pro 28 TW Zoom



Manufacturer	**Expolite**
Type	**Strobe**
DMX modes	**3**
DMX footprint	**1, 6, 10 channels**
Beam angle	**8-40°**
Size (W × H × D)	**220 × 334 × 191 mm**
GDTF fixture type	**2601CEAE-FF30-4C26-AC00-23…**

Controls

Zoom · Extra LED colours · Colour wheel · Strobe · Dimmer

Safety-relevant functions

Fixture reset · Strobe

DMX modes

UNO	1 ch
STD-W	6 ch
STD-P	10 ch

UNO

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–24 0% 25–50 10% 51–62 20% 63–75 25% 76–101 30% 102–126 40% 127–152 50% 153–177 60% 178–190 70% 191–203 75% 204–228 80% 229–254 90% 255–255 100%

STD-W

6 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–24 0% 25–50 10% 51–62 20% 63–75 25% 76–101 30% 102–126 40% 127–152 50% 153–177 60% 178–190 70% 191–203 75% 204–228 80% 229–254 90% 255–255 100%
2	Dummy	0	
3	Color Wheel	0	0–10 Open (wheel slot 1) 11–50 3200K (wheel slot 2) 51–80 3400K (wheel slot 3) 81–110 4200K (wheel slot 4) 111–140 4900K (wheel slot 5) 141–255 5600K (wheel slot 6)
4	Shutter / Strobe	0	0–9 Shutter Open 11–125 Strobe Slow 126–252 Strobe Medium 253–255 Strobe Fast
5	Zoom	128	0–127 narrow (8 Deg) 128–254 medium (24 Deg) 255–255 wide (40 Deg)
6	Zoom Reset	0	0–200 No Function (1) 201–220 Zoom Reset 221–255 No Function (2)

STD-P

10 channels

Ch	Function	Default	DMX values

STD-P (continued)

Ch	Function	Default	DMX values
1	Dimmer	0	0–24 0% 25–50 10% 51–62 20% 63–75 25% 76–101 30% 102–126 40% 127–152 50% 153–177 60% 178–190 70% 191–203 75% 204–228 80% 229–254 90% 255–255 100%
2	Dummy	0	
3	Color Add WW	0	
4	Color Add WW Fine	0	Fine byte of Color Add WW
5	Color Add CW	0	
6	Color Add CW Fine	0	Fine byte of Color Add CW
7	Color Wheel	0	0–10 Open (wheel slot 1) 11–30 Yellow (wheel slot 2) 31–50 Fern Green (wheel slot 3) 51–70 Sea Green (wheel slot 4) 71–90 Lavender (wheel slot 5) 91–110 Violet (wheel slot 6) 111–130 Pink (wheel slot 7) 131–150 light Red (wheel slot 8) 151–170 light Blue (wheel slot 9) 171–200 White RGBW (wheel slot 10) 201–205 3200K (wheel slot 11) 206–210 3400K (wheel slot 12) 211–215 4200K (wheel slot 13) 216–220 4900K (wheel slot 14) 221–225 5600K (wheel slot 15) 226–230 5900K (wheel slot 16) 231–235 6500K (wheel slot 17) 236–240 7200K (wheel slot 18) 241–245 8000K (wheel slot 19) 246–250 8500K (wheel slot 20) 251–255 10000K (wheel slot 21)
8	Shutter / Strobe	0	0–10 Shutter Open 11–125 Strobe Slow 126–252 Strobe Medium 253–255 Strobe Fast
9	Zoom	128	0–127 narrow (8 Deg) 128–254 medium (24 Deg) 255–255 wide (40 Deg)
10	Zoom Reset	0	0–200 No Function (1) 201–220 Zoom Reset 221–255 No Function (2)