Fine Art

FINE 400D LEKO



Manufacturer	**Fine Art**
Type	**Profile spot**
DMX modes	**3**
DMX footprint	**6, 7, 10 channels**
Beam angle	**19°**
Size (W × H × D)	**226 × 714 × 552 mm**
GDTF fixture type	**B521E8DF-E58A-4DC6-BFE6-76…**

Controls

Extra LED colours · RGB colour mixing · Colour temperature · Strobe · Dimmer

Safety-relevant functions

Strobe

DMX modes

Mode1 6ch	6 ch
Mode2 7ch	7 ch
Mode 3 10CH	10 ch

Mode1 6ch

6 channels

Ch	Function	Default	DMX values
1	H SBHue	0	
2	H SBHue Fine	0	Fine byte of H SBHue
3	Chromatic Mode	0	
4	Dimmer	255	
5	Shutter / Strobe	105	6–109 shutter 110–178 min Pulse 179–179 max Pulse 186–255 Strobe Rnd
6	Function	5	0–5 NA 6–25 The fan is slow 26–50 The fan is farst 51–75 Fan automatic 76–255 NA 5

Mode2 7ch

7 channels

Ch	Function	Default	DMX values
1	H SBHue	0	
2	H SBHue Fine	0	Fine byte of H SBHue
3	Chromatic Mode	0	
4	Dimmer	255	
5	Shutter / Strobe	105	6–109 shutter 110–178 min Pulse 179–179 max Pulse 186–255 Strobe Rnd
6	Function	5	0–5 NA 6–25 The fan is slow 26–50 The fan is farst 51–75 Fan automatic 76–255 NA 5
7	C TO	0	

Mode 3 10CH

10 channels

Ch	Function	Default	DMX values
1	Dimmer	255	
2	Red	255	
3	Green	255	
4	Blue	0	
5	White	0	
6	Color Add RY	0	
7	N A	0	
8	N A	0	
9	Shutter / Strobe	105	6–109 shutter 110–178 min Pulse 179–179 max Pulse 186–255 Strobe Rnd
10	Function	5	0–5 NA 6–25 The fan is slow 26–50 The fan is farst 51–75 Fan automatic 76–255 NA 5