Flash

parACCU 620 IP WDMX



Manufacturer	**Flash**
Type	**Moving head**
DMX modes	**4**
DMX footprint	**2, 6, 8, 11 channels**
Beam angle	**15°**
Pan range	**1°**
Tilt range	**1°**
Size (W × H × D)	**180 × 138 × 180 mm**
GDTF fixture type	**3706BC04-DD99-414D-B648-04…**

Controls

Extra LED colours · RGB colour mixing · Colour temperature · Colour wheel · Dimmer

DMX modes

2ch	2 ch
6ch	6 ch
8ch	8 ch
11ch	11 ch

2ch

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	C TC	152	0–10 No function 11–240 CTC 241–255 NoFeature 1

6ch

6 channels

Ch	Function	Default	DMX values
1	Red	255	
2	Green	255	
3	Blue	255	
4	White	0	
5	Color Add RY	0	
6	UV	0	

8ch

8 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–9 Open 10–255 Shutter1Strobe 2
3	Red	255	
4	Green	255	
5	Blue	255	
6	White	0	
7	Color Add RY	0	
8	UV	0	

11ch

11 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Red	255	
3	Green	255	
4	Blue	255	
5	White	0	
6	Color Add RY	0	
7	UV	0	
8	Shutter / Strobe	0	0–9 Open 10–255 Shutter1Strobe 2
9	C TC	0	0–10 No function 11–240 CTC 241–255 NoFeature 1
10	Color Macro1	0	
11	Color Macro1Rate	0	