Flash

SPOT LED 90 DIAMOND



Manufacturer	**Flash**
Type	**Moving head**
DMX modes	**1**
DMX footprint	**15 channels**
Beam angle	**25°**
Pan range	**540°**
Tilt range	**220°**
Size (W × H × D)	**240 × 450 × 220 mm**
GDTF fixture type	**B5D7A735-2E6A-4FBC-A516-A…**

Controls

Focus · Prism · Colour wheel · Dimmer · Movement speed · Gobos · Gobo rotation

Safety-relevant functions

Fixture reset

DMX modes

15ch — 15 ch

15ch

15 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–10 Open 11–255 Shutter1Strobe 2
3	Pan	128	
4	Pan Fine	0	Fine byte of Pan
5	Tilt	128	
6	Tilt Fine	0	Fine byte of Tilt
7	Position MSpeed	0	
8	Color Wheel	0	0–19 Open (wheel slot 1) 20–39 Yellow (wheel slot 2) 40–59 Blue (wheel slot 3) 60–79 Green (wheel slot 4) 80–99 Orange (wheel slot 5) 100–119 Cyan (wheel slot 6) 120–139 Pink (wheel slot 7) 140–159 Magenta (wheel slot 8) 160–254 > 255–255 >>>
9	Gobo	0	0–9 Open (wheel slot 1) 10–19 Gobo 1 (wheel slot 2) 20–29 Gobo 2 (wheel slot 3) 30–39 Gobo 3 (wheel slot 4) 40–49 Gobo 4 (wheel slot 5) 50–59 Gobo 5 (wheel slot 6) 60–69 Gobo 6 (wheel slot 7) 70–79 Gobo 7 (wheel slot 8) 80–89 Gobo 8 (wheel slot 9) 90–179 Gobo1WheelShake 2 180–214 < 215–219 >< 220–255 >
10	Gobo 2	0	0–9 Open (wheel slot 1) 10–19 Gobo 1 (wheel slot 2) 20–29 Gobo 2 (wheel slot 3) 30–39 Gobo 3 (wheel slot 4) 40–49 Gobo 4 (wheel slot 5) 50–59 Gobo 5 (wheel slot 6) 60–69 Gobo 6 (wheel slot 7) 70–139 Gobo2WheelIndex 2 140–194 < 195–199 >< 200–255 >
11	Gobo Rotation 2	0	0–127 Gobo2Pos 1 128–190 < 191–192 >< 193–255 >
12	Focus	128	
13	Prism	0	0–127 Open (wheel slot 1) 128–136 Prism (wheel slot 2) 137–255 Prism rot (wheel slot 2)
14	Color Macro1	0	0–5 No function 6–55 Macro 1 56–105 Macro 2 106–155 Macro 3 156–205 Macro 4 206–255 Macro 5

15ch (continued)

Ch	Function	Default	DMX values
15	Control1	0	0–25 No function 26–76 Function reset 77–127 P/T reset 251–255 Reset