GLP

# Nexus Hilite



| | |
|---|---|
| Manufacturer | **GLP** |
| Type | **PAR** |
| DMX modes | **1** |
| DMX footprint | **8 channels** |
| Beam angle | **25°** |
| Size (W × H × D) | **167 × 45 × 42 mm** |
| GDTF fixture type | **20196AD1-05AC-4E2F-ABA7-42…** |

## Controls

Extra LED colours · RGB colour mixing · Colour temperature · Strobe · Dimmer

## Safety-relevant functions

Strobe

## DMX modes

M3 Normal — 8 ch

## M3 Normal

8 channels

| Ch | Function | Default | DMX values |
|---|---|---|---|
| 1 | Dimmer | 0 | 0–62 Closed<br>63–126 25%<br>127–190 50%<br>191–254 75%<br>255–255 Open |
| 2 | Shutter / Strobe | 255 | 0–4 Closed<br>5–8 Single Flash<br>9–9 Flash Single<br>10–23 Pulse Slow<br>24–38 Pulse Medium<br>39–39 Pulse Fast<br>40–53 Pulse Open Slow<br>54–68 Pulse Open Med<br>69–69 Pulse Open Fast<br>70–83 Pulse Close Slow<br>84–98 Pulse Close Med<br>99–99 Pulse Close Fast<br>100–113 Double Flash Slow<br>114–128 Double Flash Med<br>129–129 Double Flash Fast<br>130–143 Random Pixel Slow<br>144–158 Random Pixel Med<br>159–159 Random Pixel Fast<br>160–178 Random All Slow<br>179–198 Random All Med<br>199–199 Random All Fast<br>200–224 Strobe Slow<br>225–249 Strobe Med<br>250–250 Strobe Fast<br>255–255 Open |
| 3 | Red | 255 | |
| 4 | Green | 255 | |
| 5 | Blue | 255 | |
| 6 | C TC | 0 | 0–9 Open White Point<br>10–69 10000K<br>70–114 8000K<br>115–140 6500K<br>141–188 5600K<br>189–203 4000K<br>204–212 3500K<br>213–217 3200K<br>218–226 3000K<br>227–238 2700K<br>239–254 2300K<br>255–255 1800K |
| 7 | Tint | 0 | 0–9 Open<br>10–132 Full Minus Green<br>133–254 Neutral<br>255–255 Full Plus Green |
| 8 | Color RGBQuality | 0 | 0–254 High Brightness<br>255–255 High Quality |