Kadence

LED Atomic Strobe



Manufacturer	**Kadence**
Type	**Strobe**
DMX modes	**1**
DMX footprint	**15 channels**
Beam angle	**126°**
Size (W × H × D)	**90 × 1 × 80 mm**
GDTF fixture type	**DBA9D3AF-2B5F-416B-AFB9-4…**

Controls

Extra LED colours · RGB colour mixing · Dimmer

DMX modes

15 Channels Mode — 15 ch

15 Channels Mode

15 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–0 Min 1–254 Min > Max 255–255 Max
2	Strobe Mode Strobe	0	0–30 No flash/Closed 31–100 Strobe slow to fast 101–130 Open 131–200 Random strobe slow to fast 201–255 Open
3	Red	255	
4	Green	255	
5	Blue	255	
6	White	0	
7	Dummy	0	
8	Video Hue Shift	0	
9	Color RGBRed	0	
10	Color RGBGreen	0	
11	Color RGBBlue	0	
12	Color Add CW	0	
13	Position Effect	0	0–10 No Function 11–15 FX 1 16–20 FX 2 21–25 FX 3 26–30 FX 4 31–35 FX 5 36–40 FX 6 41–45 FX 7 46–50 FX 8 51–55 FX 9 56–60 FX 10 61–65 FX 11 66–70 FX 12 71–75 FX 13 76–80 FX 14 81–85 FX 15 86–90 FX 16 91–95 FX 17 96–100 FX 18 101–105 FX 19 106–110 FX 20 111–115 FX 21 116–120 FX 22 121–125 FX 23 126–205 RESERVED(TBD) 206–255 Random pixel(with density)
14	Position Effect Rate	0	0–50 Static indexing 51–255 From slow to fast
15	Dimmer Mode	0	0–51 From MENU 52–101 Mode OFF 102–152 Mode 1 153–203 Mode 2 204–255 Mode 3