Martin Professional

Rush Blinder 1 WW



Manufacturer	**Martin Professional**
Type	**Blinder**
DMX modes	**3**
DMX footprint	**1, 4, 8 channels**
Beam angle	**70°**
Size (W × H × D)	**350 × 350 × 100 mm**
GDTF fixture type	**358DC4A7-103F-4F53-A6CF-42…**

Controls

Strobe · Dimmer

Safety-relevant functions

Service functions

DMX modes

1 Chan	1 ch
4 Chan	4 ch
8 Chan	8 ch

1 Chan

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

4 Chan

4 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Dimmer	0	0–254 Closed 255–255 Open
3	Dimmer	0	0–254 Closed 255–255 Open
4	Dimmer	0	0–254 Closed 255–255 Open

8 Chan

8 channels

Ch	Function	Default	DMX values
1	Shutter / Strobe	10	0–7 Shutter Closed 8–15 Shutter Open 16–69 Strobe Effect Slow 70–99 Strobe Effect Med 100–131 Strobe Effect Fast 132–139 On 140–180 Fast Close and Slow Open strobe · Slow 181–181 Fast Close and Slow Open strobe · Fast 182–189 On 3 190–230 Fast Open Slow Close strobe · Slow 231–231 Fast Open Slow Close strobe · Fast 232–239 On 2 240–246 Random Strobe · Slow 247–247 Random Strobe · Fast 248–255 Shutter Open 2
2	Dimmer	0	0–254 Closed 255–255 Open
3	Dimmer Fine	0	Fine byte of Dimmer
4	Control1	0	0–59 Reserved 60–64 Linear Curve 65–69 Square Law Curve 70–74 Inverse Square Law Curve 75–79 S-Curve 80–134 NoFeature 1 135–139 Smoothing On 140–144 Smoothing Off 145–149 Auto Blackout On 150–154 Auto Blackout Off 155–159 Control Display On 160–164 Control Display Off 165–255 NoFeature 2
5	Dimmer	255	0–254 Closed 255–255 Open
6	Dimmer	255	0–254 Closed 255–255 Open
7	Dimmer	255	0–254 Closed 255–255 Open

8 Chan (continued)

Ch	Function	Default	DMX values
8	Dimmer	255	0–254 Closed 255–255 Open