Meanreal

B 1218Par IP



Manufacturer	**Meanreal**
Type	**Effect light**
DMX modes	**4**
DMX footprint	**2, 6, 8, 11 channels**
Beam angle	**39.992996°**
Size (W × H × D)	**230 × 200 × 90 mm**
GDTF fixture type	**29383A08-95E7-499A-A55C-92…**

Controls

Extra LED colours · RGB colour mixing · Colour temperature · Effect speed · Strobe · Dimmer

Safety-relevant functions

Built-in effect programmes

DMX modes

2CH	2 ch
6CH	6 ch
8CH	8 ch
11CH	11 ch

2CH

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	C TC	11	0–10 NoFeature 11–20 2000K 21–30 2200K 31–40 2400K 41–50 2600K 51–60 2800K 61–70 3200K 71–80 3600K 81–90 4000K 91–100 4400K 101–110 4800K 111–120 5200K 121–130 5600K 131–140 6000K 141–150 6400K 151–160 6800K 161–170 7200K 171–180 7600K 181–190 8000K 191–200 8400K 201–210 8800K 211–220 9200K 221–230 9600K 231–240 10000K 241–255 NoFeature#2

6CH

6 channels

Ch	Function	Default	DMX values
1	Red	255	0–0 Min 1–254 Min > Max 255–255 Max
2	Green	255	0–0 Min 1–254 Min > Max 255–255 Max
3	Blue	255	0–0 Min 1–254 Min > Max 255–255 Max
4	White	255	0–0 Min 1–254 Min > Max 255–255 Max
5	Color Add RY	255	0–0 Min 1–254 Min > Max 255–255 Max
6	UV	255	0–0 Min 1–254 Min > Max 255–255 Max

8CH

8 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

8CH (continued)

Ch	Function	Default	DMX values
2	Shutter / Strobe	0	0–9 Shutter Open 10–10 FLASH RATE · Slow 1 Hz 11–249 FLASH RATE · Slow > Fast 1.08–19.5 Hz 250–255 FLASH RATE · Fast 19.6–20 Hz
3	Red	255	0–0 Min 1–254 Min > Max 255–255 Max
4	Green	255	0–0 Min 1–254 Min > Max 255–255 Max
5	Blue	255	0–0 Min 1–254 Min > Max 255–255 Max
6	White	255	0–0 Min 1–254 Min > Max 255–255 Max
7	Color Add RY	255	0–0 Min 1–254 Min > Max 255–255 Max
8	UV	255	0–0 Min 1–254 Min > Max 255–255 Max

11CH

11 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Red	255	0–0 Min 1–254 Min > Max 255–255 Max
3	Green	255	0–0 Min 1–254 Min > Max 255–255 Max
4	Blue	255	0–0 Min 1–254 Min > Max 255–255 Max
5	White	255	0–0 Min 1–254 Min > Max 255–255 Max
6	Color Add RY	255	0–0 Min 1–254 Min > Max 255–255 Max
7	UV	255	0–0 Min 1–254 Min > Max 255–255 Max
8	Shutter / Strobe	0	0–9 Shutter Open 10–10 FLASH RATE · Slow 1 Hz 11–249 FLASH RATE · Slow > Fast 1.08–19.5 Hz 250–255 FLASH RATE · Fast 19.6–20 Hz

11CH (continued)

Ch	Function	Default	DMX values
9	C TC	0	0–10 Disable 11–20 2000K 21–30 2200K 31–40 2400K 41–50 2600K 51–60 2800K 61–70 3200K 71–80 3600K 81–90 4000K 91–100 4400K 101–110 4800K 111–120 5200K 121–130 5600K 131–140 6000K 141–150 6400K 151–160 6800K 161–170 7200K 171–180 7600K 181–190 8000K 191–200 8400K 201–210 8800K 211–220 9200K 221–230 9600K 231–240 10000K 241–255 Disabled#2
10	Effect	0	0–9 Disabled 10–50 Static Color (Device Setting) 51–100 Jump Color 101–150 Gradient Fade Color 151–200 Mutation Pattern 201–215 Color Changing Voice Control 216–230 Color Strobe Voice Control 231–245 Mutant Voice Control 246–255 Breathing Voice Control
11	Effect Speed	0	0–0 Disabled 1–1 Min 2–254 Min > Max 255–255 Max