OGSON fixtures

ACME EYEFLASH 2 WW



Manufacturer	**OGSON fixtures**
Type	**Blinder**
DMX modes	**4**
DMX footprint	**1, 2, 4, 6 channels**
Beam angle	**96°**
Size (W × H × D)	**305 × 145 × 192 mm**
GDTF fixture type	**920C67BF-3FD4-4821-BC24-50…**

Controls

Extra LED colours · Strobe · Dimmer

DMX modes

Mode 1 1ch	1 ch
Mode 2 2ch	2 ch
Mode 3 4ch	4 ch
Mode 4 6ch	6 ch

Mode 1 1ch

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

Mode 2 2ch

2 channels

Ch	Function	Default	DMX values
1	Color Add WW	255	
2	Color Add WW	255	

Mode 3 4ch

4 channels

Ch	Function	Default	DMX values
1	Color Add WW	255	
2	Color Add WW	255	
3	Dimmer	255	0–254 Closed 255–255 Open
4	Shutter / Strobe	255	0–5 Open 6–122 min Strobe 123–123 max Strobe 124–127 Open2 128–185 Shutter Random · Shutter Ran 10–13 Hz 186–190 Open3 191–249 Shutter Random2 · Shutter Ran2 15–20 Hz 250–255 Open4

Mode 4 6ch

6 channels

Ch	Function	Default	DMX values
1	Color Add WW	255	
2	Color Add WW Fine	255	Fine byte of Color Add WW
3	Color Add WW	255	
4	Color Add WW Fine	255	Fine byte of Color Add WW
5	Dimmer	255	0–254 Closed 255–255 Open
6	Shutter / Strobe	252	0–5 Open 6–122 min Strobe 123–123 max Strobe 124–127 Open2 128–185 Shutter Random · Shutter Ran 10–13 Hz 186–190 Open3 191–249 Shutter Random2 · Shutter Ran2 15–20 Hz 250–255 Open4