Pluslite

SAGOMA PROFILE PL300SAPTZ



Manufacturer	**Pluslite**
Type	**Profile spot**
DMX modes	**4**
DMX footprint	**1, 2, 4, 5 channels**
Beam angle	**14°**
Size (W × H × D)	**221 × 459 × 342 mm**
GDTF fixture type	**1F5B1D82-53DB-432F-B8C5-27…**

Controls

Extra LED colours · Dimmer

Safety-relevant functions

Strobe

DMX modes

1 Ch mode	1 ch
2 Ch mode	2 ch
3 Ch mode	4 ch
5 Ch mode	5 ch

1 Ch mode

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	

2 Ch mode

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	
2	Temp	10	0–9 no function 10–19 2800K 20–29 3000K 30–39 3200K 40–49 3600K 50–59 4000K 60–69 4200K 70–79 4500K 80–89 4800K 90–99 5200K 100–109 5600K 110–119 6500K 120–255 no function

3 Ch mode

4 channels

Ch	Function	Default	DMX values
1	Dimmer	0	
2	Reserved 2	0	
3	Color Add WW	0	
4	Color Add CW	0	

5 Ch mode

5 channels

Ch	Function	Default	DMX values
1	Dimmer	0	
2	Temp	10	0–9 no function 10–19 2800K 20–29 3000K 30–39 3200K 40–49 3600K 50–59 4000K 60–69 4200K 70–79 4500K 80–89 4800K 90–99 5200K 100–109 5600K 110–119 6500K 120–255 no function
3	Color Add WW	0	
4	Color Add CW	0	
5	Shutter / Strobe	0	