PR LIGHTING

LSE_XLED 4022RZ (pr 8541)



Manufacturer	**PR LIGHTING**
Type	**Moving head**
DMX modes	**1**
DMX footprint	**30 channels**
Beam angle	**5-40°**
Pan range	**540°**
Tilt range	**220°**
Size (W × H × D)	**240 × 450 × 220 mm**
GDTF fixture type	**8560DD87-3946-45BA-A560-C1…**

Controls

Zoom · Extra LED colours · RGB colour mixing · Colour temperature · Colour wheel · Strobe · Dimmer

Safety-relevant functions

Fixture reset · Strobe

DMX modes

Default 30 ch

Default

30 channels

Ch	Function	Default	DMX values
1	Pan	128	
2	Pan Fine	0	Fine byte of Pan
3	Tilt	128	
4	Tilt Fine	0	Fine byte of Tilt
5	Zoom	0	
6	Zoom Fine	0	Fine byte of Zoom
7	Rotation	0	0–127 0-51 128–190 >>> 191–193 Fixe 194–255 <<<
8	Rotation Fine	0	Fine byte of Rotation
9	P TSpeed	0	
10	Fixture Global Reset	0	0–199 nothing 200–255 reset
11	Dimmer	0	0–254 Closed 255–255 Open
12	Shutter / Strobe	0	0–15 open 16–131 strobe0-100 132–139 open 140–181 pulse 182–189 0pen 190–231 pulse strobe 232–239 open 240–247 random strobe 248–255 open
13	Red	0	
14	Green	0	
15	Blue	0	
16	White	0	
17	C TO	0	
18	Color Macro1	0	

Default (continued)

Ch	Function	Default	DMX values
19	Color FXMacro	0	0–9 No FX 10–19 FX 1 20–29 FX 2 30–39 FX 3 40–49 FX 4 50–59 FX 5 60–69 FX 6 70–79 FX 7 80–89 FX 8 90–99 FX 9 100–109 FX 10 110–119 FX 11 120–129 FX 12 130–139 FX 13 140–149 FX 14 150–159 FX 15 160–169 FX 16 170–179 FX 17 180–189 FX 18 190–199 FX 19 200–209 FX 20 210–219 FX 21 220–229 FX 22 230–239 FX 23 240–249 FX 24 250–255 FX 25
20	F XSpeed	0	0–63 Static 64–158 Fast to slow 159–255 Slow to fast
21	Color Macro Changing	0	
22	Color Fore Red	0	
23	Color Fore Green	0	
24	Color Fore Blue	0	
25	Color Fore White	0	
26	Color Fore Dimmer	0	
27	Color Back Dimmer	0	
28	Color Fore Strobe	0	0–15 Open 16–131 Strob 132–139 Open 140–181 Pulse 1 182–189 Open 190–231 Pulse 2 232–239 Open 240–247 Random 248–255 Open
29	Color Back Strobe	0	0–15 Open 16–131 Strobe 132–139 Open 140–181 Pulse 1 182–189 Open 190–231 Pulse 2 232–239 Open 240–247 Random 248–255 Open
30	Dimmer Curve	0	0–0 nothing 1–63 curve1 64–127 curve2 128–191 curve3 192–255 curve4