Prolights

DisplayCobWW_30



Manufacturer	**Prolights**
Type	**Moving head**
DMX modes	**3**
DMX footprint	**1, 2, 5 channels**
Beam angle	**60°**
Pan range	**360°**
Tilt range	**320°**
Size (W × H × D)	**124 × 163 × 118 mm**
GDTF fixture type	**319BA4CF-845C-44ED-A942-06…**

Controls

Effect speed · Strobe · Dimmer

Safety-relevant functions

Built-in effect programmes

DMX modes

1ch	1 ch
2ch	2 ch
5ch	5 ch

1ch

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

2ch

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	10	0–10 NoFeature 11–255 Strobe · Slow2Fast 0.9–15 Hz

5ch

5 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	10	0–10 NoFeature 11–255 Strobe · Slow2Fast 0.9–15 Hz
3	Effect	0	0–10 NoFeature 11–90 AutoProgram_1 91–170 AutoProgram_2 171–255 AutoProgram_3
4	Effect Speed	0	
5	Dimmer Mode	0	0–51 AsFromMenu 52–101 OFF 102–152 Fast 153–203 Middle 204–255 Slow