Prolights

Polar3000



Manufacturer	**Prolights**
Type	**Moving head**
DMX modes	**4**
DMX footprint	**1, 3, 5, 11 channels**
Beam angle	**100°**
Pan range	**360°**
Tilt range	**360°**
Size (W × H × D)	**418 × 81 × 187 mm**
GDTF fixture type	**411C65B4-30AB-47C9-8E41-9D…**

Controls

Effect speed · Strobe · Dimmer

Safety-relevant functions

Built-in effect programmes

DMX modes

6ch	1 ch
3ch	3 ch
5ch	5 ch
11ch	11 ch

6ch

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

3ch

3 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–0 Open 1–255 Strobe · Slow2Fast 0.6–15 Hz
3	Dimmer Mode	0	0–51 AsFromMenu 52–101 Off 102–152 Mode 1 153–203 Mode 2 204–255 Mode 3

5ch

5 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–0 Open 1–255 Strobe · Slow2Fast 0.6–15 Hz
3	Effect	0	0–10 NoFeature 11–40 Program 1 41–70 Program 2 71–100 Program 3 101–130 Program 4 131–160 Program 5 161–190 Program 6 191–220 Program 7 221–255 Program 8
4	Effect Speed	0	
5	Dimmer Mode	0	0–51 AsFromMenu 52–101 Off 102–152 Mode 1 153–203 Mode 2 204–255 Mode 3

11ch

11 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Reserved 2	0	
3	Reserved 3	0	
4	Reserved 4	0	
5	Reserved 5	0	
6	Reserved 6	0	

11ch (continued)

Ch	Function	Default	DMX values
7	Effect	0	0–10 NoFeature 11–40 Program 1 41–70 Program 2 71–100 Program 3 101–130 Program 4 131–160 Program 5 161–190 Program 6 191–220 Program 7 221–255 Program 8
8	Effect Speed	0	
9	Dimmer	0	0–254 Closed 255–255 Open
10	Shutter / Strobe	0	0–0 Open 1–255 Strobe · Slow2Fast 0.6–15 Hz
11	Dimmer Mode	0	0–51 AsFromMenu 52–101 Off 102–152 Mode 1 153–203 Mode 2 204–255 Mode 3