Prolights

StudioCobDY_15



Manufacturer	**Prolights**
Type	**Moving head**
DMX modes	**3**
DMX footprint	**1, 5 channels**
Beam angle	**15.34°**
Pan range	**360°**
Tilt range	**360°**
Size (W × H × D)	**192 × 238 × 188 mm**
GDTF fixture type	**EFD27669-9933-4808-859E-903…**

Controls

Effect speed · Strobe · Dimmer

Safety-relevant functions

Strobe · Built-in effect programmes

DMX modes

1ch	1 ch
2ch	5 ch
5ch	5 ch

1ch

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

2ch

5 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Reserved 2	0	
3	Reserved 3	0	
4	Reserved 4	0	
5	Shutter / Strobe	0	0–10 Open 11–254 Slow Strobe 255–255 Fast Strobe

5ch

5 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–10 Open 11–254 Slow Strobe 255–255 Fast Strobe
3	Effect	0	0–10 NoFeature 11–90 Effect1 91–170 Effect2 171–255 Effect3
4	Effect Speed	0	0–254 SlowRate 255–255 FastRate
5	Dimmer Mode	0	0–10 As From Menu 11–51 NoFeature 52–101 Linear 102–152 NonLinear curve 1 (Fast) 153–203 NonLinear curve 1 (Mid) 204–255 NonLinear curve 1 (Slow)