
Prolights

StudioCobPlusDY2_37



Manufacturer	**Prolights**
Type	**Moving head**
DMX modes	**3**
DMX footprint	**1, 2, 5 channels**
Beam angle	**37.2°**
Pan range	**360°**
Tilt range	**360°**
Size (W × H × D)	**210 × 257 × 186 mm**
GDTF fixture type	**4B7D4874-F81D-4447-9581-AB…**

Controls

Effect speed · Strobe · Dimmer

Safety-relevant functions

Built-in effect programmes

DMX modes

1ch	1 ch
2ch	2 ch
5ch	5 ch

1ch

1 channel

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open

2ch

2 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–30 Open 31–100 Strobe · Slow2Fast 0.9–15 Hz 101–130 Opoen 131–200 Random · Slow2Fast 0.9–15 Hz 210–255 Open

5ch

5 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–254 Closed 255–255 Open
2	Shutter / Strobe	0	0–30 Open 31–100 Strobe · Slow2Fast 0.9–15 Hz 101–130 Opoen 131–200 Random · Slow2Fast 0.9–15 Hz 210–255 Open
3	Effect	0	0–10 NoFeature 11–70 AutoProgram1 71–130 AutoProgram2 131–190 AutoProgram3 191–255 AutoProgram4
4	Effect Speed	0	
5	Dimmer Mode	0	0–51 AsFromMenu 52–101 Off 102–152 Fast 153–203 Mid 204–255 Slow