PRstage

F400Z



Manufacturer	**PRstage**
Type	**Moving head**
DMX modes	**2**
DMX footprint	**11, 13 channels**
Beam angle	**7-53°**
Pan range	**540°**
Tilt range	**270°**
Size (W × H × D)	**230 × 320 × 230 mm**
GDTF fixture type	**B622E369-8414-4203-9217-6A8…**

Controls

Zoom · Extra LED colours · Colour temperature · Strobe · Dimmer · Pan and tilt · Movement speed

Safety-relevant functions

Fixture reset

DMX modes

Mode 2 - 11CH	11 ch
Mode 3 - 13CH	13 ch

Mode 2 - 11CH

11 channels

Ch	Function	Default	DMX values
1	Dimmer	0	0–253 Closed 254–255 Open
2	Dimmer Fine	0	Fine byte of Dimmer
3	Shutter / Strobe	0	0–3 Open 4–202 Min Strobe 203–203 Max Strobe 204–254 Random Strobe Min 255–255 StrobeRandom · Empty Channel Max 25 Hz
4	White	255	
5	C TO	0	0–254 5800 K (wheel slot 1) 255–255 3200 K (wheel slot 2)
6	Pan	128	
7	Pan Fine	128	Fine byte of Pan
8	Tilt	128	
9	Tilt Fine	128	Fine byte of Tilt
10	Zoom	0	
11	Control1	0	0–149 NoFeature 150–159 Fast Dimmer (Wait 3S) 160–169 Slow Dimmer (Wait 3S) 170–249 NoFeature 1 250–255 Global Reset (Wait 3S)

Mode 3 - 13CH

13 channels

Ch	Function	Default	DMX values
1	Pan	128	
2	Pan Fine	128	Fine byte of Pan
3	Tilt	128	
4	Tilt Fine	128	Fine byte of Tilt
5	Position MSpeed	0	
6	Zoom	0	
7	Dimmer	0	0–253 Closed 254–255 Open
8	Dimmer Fine	0	Fine byte of Dimmer
9	Shutter / Strobe	0	0–3 Open 4–202 Min Strobe 203–203 Max Strobe 204–254 Random Strobe Min 255–255 StrobeRandom · Empty Channel Max 25 Hz
10	White	255	
11	C TO	0	0–254 5800 K (wheel slot 1) 255–255 3200 K (wheel slot 2)
12	Dimmer Curve	0	0–49 Linear Dimming 50–99 Square-Law Dimming 100–149 Inverse Square-Law Dimming 150–255 S curve Dimming
13	Control1	0	0–149 NoFeature 150–159 Fast Dimmer (Wait 3S) 160–169 Slow Dimmer (Wait 3S) 170–249 NoFeature 1 250–255 Global Reset (Wait 3S)