Wisdom

Liunar Beam Gian-Carlo v1



Manufacturer	**Wisdom**
Type	**Moving head**
DMX modes	**1**
DMX footprint	**20 channels**
Beam angle	**25°**
Pan range	**540°**
Tilt range	**270°**
Size (W × H × D)	**240 × 450 × 220 mm**
GDTF fixture type	**DC2554F6-24CB-446A-B874-63…**

Controls

Focus · Frost · Prism · Prism rotation · Colour wheel · Dimmer · Movement speed · Gobos

Safety-relevant functions

Lamp on and off · Fixture reset · Built-in effect programmes

DMX modes

20 Ch — 20 ch

20 Ch

20 channels

Ch	Function	Default	DMX values
1	Pan	128	
2	Tilt	128	
3	Pan Fine	0	Fine byte of Pan
4	Tilt Fine	0	Fine byte of Tilt
5	Position MSpeed	0	
6	Gobo2Select Effects	0	0–127 NO RAINBOW 128–255 RAINBOW
7	Shutter1Strobe	255	0–19 CLOSED 20–39 STROBE 1 40–59 STROBE 2 60–79 STROBE 3 80–99 STROBE 4 100–229 STROBE 5 230–254 STROBE RANDOM 255–255 OPEN
8	Dimmer	0	0–24 ZERO 25–51 10% 52–76 20% 77–101 30% 102–126 40% 127–152 50% 153–177 60% 178–202 70% 203–229 80% 230–254 90% 255–255 100%
9	Color1Wheel Index	0	0–9 OPEN GOBO (wheel slot 1) 10–19 RED (wheel slot 2) 20–29 YELLOW (wheel slot 3) 30–39 BLU (wheel slot 4) 40–49 GREEN (wheel slot 5) 50–59 ORANGE (wheel slot 6) 60–69 MAGENTA (wheel slot 7) 70–79 AMBER (wheel slot 8) 80–89 YELLOW STRAW (wheel slot 9) 90–99 AZZURE (wheel slot 10) 100–109 LIME (wheel slot 11) 110–119 CTO (wheel slot 12) 120–129 CTB (wheel slot 13) 130–255 UV (wheel slot 14)
10	Gobo1Select Spin	0	0–4 OPEN GOBO (wheel slot 1) 5–9 RIDUCTION 1 (wheel slot 2) 10–14 CIRCLE DOTS (wheel slot 4) 15–19 FAN (wheel slot 5) 20–24 HEART (wheel slot 6) 25–29 SPIKES (wheel slot 7) 30–34 FAN 2 (wheel slot 8) 35–39 CIRCLE DOTS 2 (wheel slot 9) 40–44 DOTS (wheel slot 10) 45–49 FLOWER (wheel slot 11) 50–54 STRIPES (wheel slot 12) 55–59 3 TUNNELS (wheel slot 13) 60–64 DOTS (wheel slot 13) 65–69 STAR (wheel slot 15) 70–129 ROTATION CCW 130–134 STOP 135–185 ROTATION CW 186–255 SHAKE

20 Ch (continued)

Ch	Function	Default	DMX values
11	Prism	0	0–127 NO PRISM 128–255 PRISM 1 (wheel slot 1)
12	Prism Rotation	0	0–127 SPIN INDEX 128–190 SPIN MED / FST CW 191–192 STOP SPIN 193–255 SPIN MED / FST CCW
13	Focus	0	0–69 0% FOCUS 70–127 25% FOCUS 128–191 50% FOCUS 192–254 75% FOCUS 255–255 100% FOCUS
14	Frost1	0	0–127 NO FROST 128–255 FROST
15	Dimmer Mode	0	
16	Animation System1Macro	0	
17	Color Macro1Rate	0	
18	Effect	0	0–127 RING DIRECTION CW 128–255 RING DIRECTION CCW
19	Effects1Adjust1	0	
20	Fixture Global Reset	0	0–99 NO RESET 100–110 LAMP OFF 5 SECS 111–199 NULL 200–210 LAMP ON 5 SECS 211–249 NULL 250–255 RESET ALL 5 SECS